Architectural hinges IVES



3CB1HW 3 Knuckle, concealed bearing, heavy weight full mortise hinge

- Recommended for heavier weight doors (>150 lbs)
- Recommended for high frequency usage (400 cycles per day)
- Made with two heavy duty concealed nylon bearings
- Recommended for use with a door closer
- Packed with fasteners for hollow metal and wood doors 12-24 x 1/2 UFPHMS, 12 x 1 1/4 FPHWS

Certifications

- Certified to ANSI/BHMA A156.1 for performance standards
- Meets ANSI/BHMA 156.7 for template hinge dimensions
- UL Classified for windstorm rated assemblies - R37965
- UL Listed, 3 hour fire doors

Material substrate

 Made from brass, 1040 steel, or 304 series stainless steel

Options

•	NRP	.Non-removable pin
÷	HT	.Hospital tip
÷	SH	.Security stud - comes

- standard with NRP

 RC-1/4, RC-5/8....Rounded corners

 SECSecurity fasteners –
 pin-in-socket
- TW4.....Four wire
- TW4M.....Four wire with monitor
- TW8.....Eight wire
- TW8MEight wire with monitor
- MON......Monitor

Dimensions

Height x Width	Size (mm)	Gauge	
4.5 x 4	114 x 102	0.180	
4.5 x 4.5	114 x 114	0.180	
5 x 4.5	127 x 114	0.190	
5 x 5	127 x 127	0.190	

Refer to General Hinge Information page to determine proper hinge for application

3CB1HW Finishes

ВНМА	Description	Substrate	Finish
600	Primer paint	Steel	USP
605	Bright brass	Brass	US3
606	Satin brass	Brass	US4
610	Satin bronze	Brass	US10
613	Oil rubbed bronze	Brass	US10B
614	Oxidized bronze	Brass	US10A
616	Blackened bronze	Brass	US11
619	Satin nickel	Brass	US15
622	Matte black	Brass	B-BLK
625	Bright chrome	Brass	US26
626	Satin chrome	Brass	US26D
643e/716	Aged bronze	Brass	B-643e/716
629	Bright stainless	Stainless steel	US32
630	Satin stainless	Stainless steel	US32D
631	Matte black	Steel	F-BLK
632	Bright brass	Steel	US3
633	Satin brass	Steel	US4
639	Satin bronze	Steel	US10
640	Oil rubbed bronze	Steel	US10B
641	Oxidized bronze	Steel	US10A
643	Blackened bronze	Steel	US11
646	Satin nickel	Steel	US15
651	Bright chrome	Steel	US26
652	Satin chrome	Steel	US26D
643e/716	Aged bronze	Steel	F-643e/716

For other colors, consult factory.